



PACKAGE HIGHLIGHTS

- REV-XR™ platform
- **More comfortable REV-XP seat**
- Heated seat
- SC™-5 rear suspension
- Air Control Suspension (ACS)
- Lightweight 15 x 137 x 1.25-inch lug RipSaw⁺ track
- Dual A-arm front suspension
- Pilot™ 5.7 skis
- Brembo brake with braided stainless-steel brake line
- Tilt steering with 4 positions
- Multi-function digital gauge display with temperature gauge
- Electric start

- Painted tunnel
- 12V power outlet
- Heated visor power outlet
- Mirrors
- GSX expandable tunnel bag

EXTRA HIGHLIGHTS E-TEC 600 H.O. & E-TEC 800R

- RER™ electronic reverse
- ### 4-TEC 1200
- **eDrive™ 2 drive clutch**
 - Air radiator with fan
 - Electronic push-button reverse

NEW features for 2013

ENGINE CHOICE

Engine	Rotax® E-TEC® 600 H.O.	Rotax E-TEC 800R	Rotax 4-TEC® 1200
Engine details	Liquid-cooled, 3-D R.A.V.E.™	Liquid-cooled, 3-D R.A.V.E.	Liquid-cooled, four-stroke D.O.H.C., dry sump
Cylinders	2	2	3
Displacement	594.4 cc / 36.3 in ³	799.5 cc / 48.8 in ³	1170.7 cc / 71.4 in ³
Bore	72 mm / 2.8 in	82 mm / 3.2 in	91 mm / 3.6 in
Stroke	73 mm / 2.9 in	75.7 mm / 3 in	60 mm / 2.4 in
Maximum engine speed	8100 RPM	7900 RPM	7800 RPM
Carburation	Electronic Direct Injection	Electronic Direct Injection	EFI
Recommended fuel type	Premium unleaded	Premium unleaded	Regular unleaded
Minimum octane	91	91	87
Fuel tank	40 liters / 10.6 gallons	40 liters / 10.6 gallons	40 liters / 10.6 gallons
Oil tank capacity	3.7 liters / 3.9 quarts	3.7 liters / 3.9 quarts	3.5 liters / 3.7 quarts

POWERTRAIN

Drive clutch type	TRA™ III	TRA™ VII	eDrive 2
Driven clutch type	QRS	QRS	QRS
Engagement	3400 RPM	3800 RPM	2500 RPM
Small sprocket number of teeth	23	27	24
Large sprocket number of teeth	45	45	45
Drive sprocket number of teeth	8	8	8
Drive sprocket diameter	183 mm / 7.2 in	183 mm / 7.2 in	183 mm / 7.2 in
Brake system	Brembo brake with stainless-steel braided brake line	Brembo brake with stainless-steel braided brake line	Brembo brake with stainless-steel braided brake line

DRY WEIGHT

213 kg / 469 lb	219 kg / 483 lb	249 kg / 549 lb
-----------------	-----------------	-----------------

FEATURES

Frame	REV-XR	Electric start	Standard	Mirrors	Standard
Skis	Pilot 5.7	Reverse	RER (600 H.O. & 800R) Electronic (1200)	Windshield	410 mm / 16 in
Seating	REV-XP (heated)	Heated throttle lever	Standard	Carbide runner	Standard
Handlebar	Bent painted steel / Tilt steering / Steering cover	Heated grips	Standard	Carbide configuration	102 mm / 4 in square type at 90°
Riser block height	115 mm / 4.5 in	Gauge	Multi-function	Hitch	Optional

COLOR CHOICES

Pure Magnesium or Black

DIMENSIONS

Vehicle overall length	3110 mm / 122.4 in
Vehicle overall width	1217 mm / 47.9 in
Vehicle overall height	1338 mm / 52.7 in
Ski stance	1077 mm / 42.4 in
Ski overall length	1066 mm / 42 in
Track nominal width	381 mm / 15 in
Track nominal length	3487 mm / 137 in
Track profile height	31.8 mm / 1.25 in RipSaw

SUSPENSION

Front suspension	Dual A-arms
Front shock	HPG™
Front suspension max. travel	229 mm / 9 in
Rear suspension	SC-5
Center shock	HPG
Rear shock	ACS (air spring)
Rear suspension max. travel	406 mm / 16 in



1.25" RipSaw track

Great traction and supreme trail manners with this lightweight track.



Heated REV-XP seat

Two pre-set heating levels neutralize even the coldest rides.



NEW eDrive 2 drive clutch (4-TEC 1200)

More responsive acceleration and long-term durability from this all-new clutch.



Multi-function gauge with LCD screen

COLOR AVAILABLE

Pure Magnesium or Black

ENGINE CHOICE

4-TEC 1200

E-TEC 800R

E-TEC 600 H.O

GAUGE FEATURES

Speedometer Standard

Tachometer Standard

Fuel Standard

Temperature Standard

GSX SE